

SUCCESS STORIES MARGHERA LEVANTE

COMBINED CYCLE POWER PLANT

LOCATION VENICE, ITALY

CUSTOMER SELM END USER EDISON

PROJECT OVERVIEW

Gas Turbine

- + Supplier: Nuovo Pignone
- + Type: Frame 9E
- + Main Fuel: Natural Gas
- + Backup Fuel: Light Oil No. 2

HRSG

- + No. of Units: 2
- Type: Horizontal gas path Natural Circulation, 3 Pressure Levels Unfired

HP Steam Flow HP Steam Pressure HP Steam Temperature	ENGLISH 390,214 lbs/hr 624 psig 925°F	METRIC 49.17 kg/s 43.0 barg 496.1°C
Reheat Steam Flow	N/A	N/A
Reheat Steam Pressure	N/A	N/A
Reheat Steam Temperature	N/A	N/A
IP Steam Flow IP Steam Pressure IP Steam Temperature	85,098 lbs/hr 305 psig 450°F	10.72 kg/s 21.0 barg 232.2°C
LP Steam Flow	70,983 lbs/hr	8.94 kg/s
LP Steam Pressure	25 psig	1.7 barg
LP Steam Temperature	Sat.	Sat.



PERFORMANCE RESULTS

- Marghera Levante was constructed to meet the growing electricity needs of local industrial users and the overall power demand in and around Venice
- HRSGs are of the horizontal gas path natural circulation type and feature three pressure levels

VOGT POWER SOLUTION

- Units for Marghera Levante are VPI's "MSG" design. The MSG is a single wide modular box design with standard widths and a high degree of shop assembly
- The boxes come complete with installed casing, steel structure and pre-assembled internal piping
- The MSG design minimizes the number of boiler parts sent to a jobsite resulting in lower installation costs and shorter construction periods